

# TAKEX CEILING MOUNT PASSIVE SENSOR COMPARISON CHART 2024

**TAKEX**

Model	PA-6614E / PA-6614E(BL)	PA-6812E / PA-6812E(BL)	PA-6810E / PA-6810E(BL)	PA-6805E / PA-6805E(BL)	PA-6820E / PA-6820E(BL)	PA-8410E	PA-8420E
<b>Appearance</b>							
<b>Area type</b>	14m Wide angle	12m Wide angle	15m x 360°	4m Spot	20m Vertical curtain	10m Wide angle	20m Vertical curtain
<b>Coverage</b>	 [Top view] 80°	 [Top view] 84°	 [Top view] 30°	 [Top view] 45°	 [Top view] 67.5°	 [Top view] 10m	 [Top view] 2.3m
<b>Detection System</b>	Twin mirror + Dual element	Dual element	Dual element	Dual element	Dual element	4 x Dual element	4 x Dual element
<b>Method</b>	2nd Generation Fuzzy Processing	Pulse Count	Pulse Count				
<b>Mounting height</b>	6m max.	5m max.	5m max.	5m max.	5m max.	8m max.	8m max.
<b>Features</b>	<ul style="list-style-type: none"> <li>-Pet immunity</li> <li>-Self diagnosis</li> <li>-Slight motion detection mode</li> </ul>	<ul style="list-style-type: none"> <li>-LED control</li> <li>-Low cost</li> </ul>	<ul style="list-style-type: none"> <li>-LED control</li> <li>-Low cost</li> </ul>	<ul style="list-style-type: none"> <li>-LED control</li> <li>-Low cost</li> </ul>	<ul style="list-style-type: none"> <li>-LED control</li> <li>-Low cost</li> </ul>	<ul style="list-style-type: none"> <li>-High ceiling application</li> <li>-LED control</li> </ul>	<ul style="list-style-type: none"> <li>-High ceiling application</li> <li>-LED control</li> </ul>

Model	PA-7012E	PA-7030E	PA-7100E	PA-5312E	PA-5325E	PA-6412PI	PA-370
<b>Appearance</b>							
<b>Area type</b>	12m Wide angle	30m Vertical curtain	12m x 360°	12m Wide angle	25m Vertical curtain	12m Wide angle	6.7m Wide / Narrow curtain
<b>Coverage</b>	 [Top view] 80°	 [Top view] 30m	 [Top view] 12m	 [Top view] 84°	 [Top view] 25m	 [Top view] 84°	 [Front view] 6.7m
<b>Detection System</b>	Quad element	Quad element	Quad element	Quad element	Quad element	Dual element	Dual element
<b>Method</b>	Pulse Count	Pulse Count	Pulse Count	Fuzzy Processing	Fuzzy Processing	Pulse Count	Pulse Count
<b>Mounting height</b>	5m max.	5m max.	3.6m max.	4m max.	4m max.	4.9m max.	5m max.
<b>Features</b>	<ul style="list-style-type: none"> <li>-Pet immunity</li> <li>-LED control</li> </ul>	<ul style="list-style-type: none"> <li>-Pet immunity</li> <li>-LED control</li> </ul>	<ul style="list-style-type: none"> <li>-Pet immunity</li> <li>-LED control</li> </ul>	<ul style="list-style-type: none"> <li>-Pet immunity</li> <li>-LED control</li> <li>-Slight motion detection mode</li> </ul>	<ul style="list-style-type: none"> <li>-Pet immunity</li> <li>-LED control</li> <li>-Slight motion detection mode</li> </ul>	<ul style="list-style-type: none"> <li>-Pet immunity</li> <li>-Low cost</li> </ul>	<ul style="list-style-type: none"> <li>-Interchangeable lens (M,W)</li> <li>-Low cost</li> </ul>