

# PSC-1

125 kHz Standard Light Proximity Card

Pyramid Series Proximity®  
Data Sheet



**Application** - A clamshell design, ideal for access control applications where no direct physical contact is required between card and reader.

**Compatible** - Can be encoded with 26-bit Wiegand, custom Wiegand or magnetic stripe formats.

**Industry Friendly** - Can be ordered to support several proximity card and tag technologies.

**Convenience** - Pre-punched slot makes it ideal to carry on a lanyard or badge holder.

**Durable** - Manufactured from robust materials and does not require a battery.

Pyramid Series Proximity from Farpointe Data sets the electronic security benchmark for 125 kHz proximity readers, card and tags. Based upon proven contactless digital radio frequency identification (RFID) technology, Pyramid readers interface with a wide range of electronic access control systems by complying with the Wiegand communication protocol. They offer value-add features such as MAXSecure™ and fleaPower™, and can be ordered to support several proximity card and tag technologies. Additionally, Pyramid cards and tags are passive devices, eliminate maintenance by requiring no battery, and can be ordered to support several proximity reader technologies.

©2012 Farpointe Data, Inc. All rights reserved. Farpointe Data, the Farpointe Data logo, Pyramid Series Proximity, Pyramid Series logo, Ranger and Delta are registered trademarks of Farpointe Data, Inc. AWID is a trademark of Applied Wireless Identifications Group. HID and the HID logo are registered trademarks of HID Global Corporation, an ASSA ABLOY company. All other trademarks are the property of their respective owners.

232 Santa Ana Court  
Sunnyvale, CA 94085 USA  
Tel: +1-408-731-8700  
Email: [support@farpointedata.com](mailto:support@farpointedata.com)  
Website: [www.farpointedata.com](http://www.farpointedata.com)

 **Farpointe Data**®  
R e a d e r s    C r e d e n t i a l s

# PSC-1

## 125 kHz Standard Light Proximity Card

## Pyramid Series Proximity® Data Sheet

### Features and Specifications:

**Technology:** Proximity

**Frequency:** Excitation (125 kHz)

**Operation:** Passive (no battery)

**Type:** Clamshell card

**Formats:** Wiegand (26-bit and custom formats) and ABA Track II magnetic stripe (clock and data)

**OEM Label Area Dimensions:** 0.9 x 0.35 inch (22.86 x 8.89 mm), with corner radius of 0.63 inch (16 mm)<sup>1</sup>

**Dimensions (HxWxD):** 3.4 x 2.2 x 0.06 inches (86 x 55 x 1.5 mm)

**Operating Temperature:** -35° F to 122° F (-35° C to +50° C)

**Material:** ABS

**Weight:** 0.3 oz. (9g)

**Color:** Off-white

**Humidity:** 0-95% non-condensing

**Slot Punch<sup>2</sup>:** Standard, vertical slot

**Marking<sup>3</sup>:** Date code and ID

**Imaging<sup>4</sup>:** Use a glossy adhesive overlay for color dye sublimation printing or print directly on card

**Warranty:** Limited lifetime warranty

**Read Range<sup>6</sup>:** Up to 8 inches (203 mm)

**Options<sup>5</sup>:** Custom printing of company logos, URL, telephone number and more

**Technologies Supported:** PSC-1: Pyramid Series Proximity supported<sup>7</sup>  
PSC-1-H: Certain HID® Proximity protocols supported<sup>8</sup>  
PSC-1-A: Certain AWID® Proximity protocols supported<sup>9</sup>

<sup>1</sup> Consistent with OEM label area found on many Pyramid Series® and Delta® readers, as well as Ranger Transmitters®.

<sup>2</sup> Models PSM-2P, PSM-2S and PSI-4 may be ordered pre-punched with horizontal/vertical slots. Contact Farpointe or your supplier for more information.

<sup>3</sup> Matching internal and external sequential coding standard. Custom printing available.

<sup>4</sup> Please verify that the printer (or overlay) supports credential type/thickness.

<sup>5</sup> Contact Farpointe to learn how you can customize your cards and tags.

<sup>6</sup> Tested with 12VDC @ P-500 reader. Reference Card Read Range Document for additional read range information.

<sup>7</sup> Examples of supporting readers include, but are not limited to, P-300, P-400, P-500 and P-640.

<sup>8</sup> Examples of supporting readers may include, but are not limited to, ProxPointPlus®, ThinLine® II and MininProx®.

<sup>9</sup> Examples of supporting readers may include, but are not limited to, SP-6820, SR-2400 and KP-6840.

Farpointe Data reserves the right to change specifications without notice.

232 Santa Ana Court  
Sunnyvale, CA 94085 USA  
Tel: +1-408-731-8700  
Email: support@farpointedata.com  
Website: www.farpointedata.com

 **Farpointe Data**®  
Readers  Credentials