

WVC02AR4X20/WVC02AR4X50

2.0 MP/5.0 MP 2.5" MINI IP Dome PTZ



FEATURES:

- Metal Dome Pan-Tilt-Zoom IP Camera
- Pan Range: 0°~350°, Pan Speed: 25°/s, Tilt Range: 0°~70°, Tilt Speed: 20°/s
- 4X Optical Zoom Lens(f=2.8-12mm), Auto Focus lens
- 4PCS IR LED Up to 35Meters
- Support human shape detection
- Support onvif protocol, compatible with Hikvision ,dahua NVR
- Built-in Surge and Lightning Protection Devices
- Ingress Protection: IP66

MODEL	WVC02AR4X20/WVC02AR4X50
SPECIFICATION	
Image Sensor	2.0MP Starlight 3516E+SONY307/ 5.0MP 3516D+AR0521
Effective Pixels	1920(H)×1080(V)/2592(H)×1944(V)
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
IR Distance	Up to 35 Meters
Lens	4X 2.8-12mm
TV SYSTEM	PAL/NTSC,Progressive
VIDEO FRAME RATE	20fps@1080P/15fps@5MP
FOCUS	AUTO
ZOOM	Motorized
PAN RANGE	0° ~350° , Horizontal
PAN SPEED	25° /s
TILT RANGE	0° ~70° , Vertical
TILT SPEED	20° /s
QUANTITIES OF PRESETS	220
Guard Tours	3 groups (each group 16 preset,dwell time and speed selectable)
Guard Points	Max.16 points, dwell time user selectable
AB scan range	any point in range:0° ~70° and 0° -350°
AB scan speed	1-9 grades
Network protocol	TCP/IP, HTTP, DHCP, DDNS, RTP,RTSP, PPPOE ,SMTP, NTP, UPNP
Interface protocol	ONVIF Hikvision,Dahua, Meilstone and other plantforms private protocol
Network interface	Built in RJ45network interface support 10M/100M IP DATA
Application interface	Provide Linux NindoNs SDK develop bag and CGI protocol can be second fast develop
BROWSER	Support IE7 IE8 IE9 Chrome8+ Firefox3.5+ Safari5+
INGRESS PROTECTION	IP66
POWER SUPPLY	DC12V±10%
WORKING ENVIRONMENT	-30°C~+60°C / Less than 95%RH (no condensation)
Protection grade	TVS3000V lightning protection ,surge protection and voltage transient protection weather proof
Optional Choice	POE; Bracket; Audio
WEIGHT	1.1KG

DIMENSION Unit: 110*96mm

